

POWERMISSION 2 (PO29-LM059)**Luminaire Structure**

- Single cable entry
- Clear toughened glass

- Integral control gear

Optic**T2****T3****T4****Product colour**

01 - Black (RAL 9011)


02 - Dark Grey (RAL 7043)

03 - White (RAL 9003)

05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)

Special finishes upon request

SU01 - Concrete - Urban

SU02 - Softscape - Urban

SU03 - Stone - Urban


SU04 - Corten - Urban



SW01 - Oak - Woodland



SW02 - Walnut - Woodland



SW03 - Pine - Woodland

POWERMISSION 2 (PO29-LM059)

Technical information

| | |
|----------------------|-----------------------|
| Material | Aluminium |
| Light source | 24 LED |
| Power | 54 W |
| Lumen | 7677 - 8556 lm |
| Efficacy | 148 - 165 lm/W |
| Driver option | Integral control gear |

| | |
|----------------------|-----------------------------|
| Driver | Constant current (CC) |
| Input voltage | 220-240 V 50/60 Hz |
| Optic | T2, T3, T4 |
| Optic value | 145°x55°, 138°x73°, 98°x74° |
| CCT / CRI | 3000K CRI80, 4000K CRI80 |
| Dimming type | On/Off |

| | |
|---------------------------------|--|
| Product colours | Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland |
| Weight | 4.8 kg |
| Operating temperature | -20 °C to 40 °C |
| Through wiring | Single cable entry |
| Lens / Reflector / Optic | Clear toughened glass |
| Variants (On/Off) | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0) |

PO29-LM059

