

**POWERMISSION 4 (PO49-LM214)****Luminaire Structure**

- Clear toughened glass

- Integral control gear

**Optic**

T2

T3

T4

ME

**Product colour**

01 - Black (RAL 9011)


02 - Dark Grey (RAL 7043)

03 - White (RAL 9003)

05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)

**Special finishes upon request**

SU01 - Concrete - Urban


SU02 - Softscape - Urban

SU03 - Stone - Urban

SU04 - Corten - Urban



SW01 - Oak - Woodland



SW02 - Walnut - Woodland



SW03 - Pine - Woodland

**POWERMISSION 4 (PO49-LM214)**

**Technical information**

<b>Material</b>	Aluminium	<b>Driver</b>	Constant current (CC)	<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Light source</b>	96 LED	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Weight</b>	18.2 kg
<b>Power</b>	212 W	<b>Optic</b>	T2, T3, T4, ME	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Lumen</b>	19203 - 22352 lm	<b>Optic value</b>	145°x55°, 141°x72°, 97°x77°, 140°x62°	<b>Lens / Reflector / Optic</b>	Clear toughened glass
<b>Efficacy</b>	82 - 96 lm/W	<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80	<b>Variants (On/Off)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
<b>Driver option</b>	Integral control gear	<b>Dimming type</b>	On/Off, 1-10V, DALI		

**Accessories**

 <p>Single arm mounting <b>A90660</b></p>	 <p>Single arm mounting <b>A90776</b></p>	 <p>Double arm mounting <b>A90976</b></p>	 <p>Motion sensor - PIR - 1-10V - Up to 12 m <b>A90191-L7</b></p>
 <p>Motion sensor - PIR - 1-10V - Up to 6 m <b>A90191-L3</b></p>	 <p>Motion sensor - PIR - 1-10V - Up to 3 m <b>A90191-L2</b></p>	 <p>Circuit breaker box IP44 <b>A21291</b></p>	 <p>Remote controller for the motion sensor - 1-10V (A90191) <b>A90791</b></p>