

## **QUANTUM 2** (QA-50015)











# **Product description**

Medium - RGBW



#### **Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry, through wiring upon request
- Three IP68 connectors supplied with 0.2 m of 3x1.0 sqmm outdoor cable and 2x0.2 m of 2x0.5 sqmm outdoor shielded cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear toughened glass

- Integral control gear

## Optic







### **Product colour**









05 - Matt Silver (RAL 9006)





Special finishes upon request





06 - Bronze (RAL 6014)

SW01 - Oak Woodland

SU01 - Concrete Urban

SW02 - Walnut -

SW03 - Pine



## **QUANTUM 2** (QA-50015)

## **Technical information**


Material	Aluminium
Light source	18 LED
Power	77 W
Lumen	2900 - 3580 lm
Efficacy	38 - 46 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz


Optic	N, M, E
Optic value	20°, 35°, 25° x 48°
CCT / CRI	RGBW30, RGBW40
Bug	B3-U1-G0
ULR	0%
ULOR	0%
CIE flux code n°3	100
Dimming type	DMX/RDM

Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	8.5 kg
Operating temperature	-20 °C to 40 °C
Cable	Three IP68 connectors supplied with 0.2 m of 3x1.0 sqmm outdoor cable and 2x0.2 m of 2x0.5 sqmm outdoor shielded cable
Through wiring	Single cable entry, through wiring upon request
Lens / Reflector / Optic	High-efficiency PMMA lens, Clear toughened glass
Variants (DMX/RDM)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

#### QA-50015







#### **Accessories**



