

**QUARTER 2 (QU-20032)****Product description**

Medium - 2 sides

**Luminaire Structure**

- Single cable entry
- High-efficiency PMMA lens


- Clear toughened glass
- Integral control gear

**Product colour**


01 - Black (RAL 9011)    02 - Dark Grey (RAL 7043)    03 - White (RAL 9003)    05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)

**Special finishes upon request**

SU01 - Concrete - Urban    SU02 - Softscape - Urban    SU03 - Stone - Urban    SU04 - Corten - Urban



SW01 - Oak - Woodland    SW02 - Walnut - Woodland    SW03 - Pine - Woodland

**QUARTER 2 (QU-20032)**

**Technical information**

|                      |                       |
|----------------------|-----------------------|
| <b>Material</b>      | Aluminium             |
| <b>Light source</b>  | 2 x 48 LED            |
| <b>Power</b>         | 150 W                 |
| <b>Lumen</b>         | 17628 - 20158 lm      |
| <b>Efficacy</b>      | 118 - 134 lm/W        |
| <b>Driver option</b> | Integral control gear |

|                      |  |
|----------------------|--|
| <b>Driver</b>        | Constant current (CC)  |
| <b>Input voltage</b> | 220-240 V 50/60 Hz   |
| <b>Optic</b>         | M, W, EW, T1, T2, T3, T4, ME                                     |
| <b>Optic value</b>   | 30°, 56°, 112°, 145°x75°, 136°x58°, 123°x93°, 105°x69°, 140°x63° |
| <b>CCT / CRI</b>     | 3000K CRI80, 4000K CRI80   |
| <b>Dimming type</b>  | On/Off, 1-10V, DALI  |

|                                       |  |
|---------------------------------------|--|
| <b>Product colours</b>                | Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland |
| <b>Weight</b>                         | 23.7 kg  |
| <b>Operating temperature</b>          | -20 °C to 40 °C  |
| <b>Through wiring</b>                 | Single cable entry   |
| <b>Lens / Reflector / Optic</b>       | High-efficiency PMMA lens, Clear toughened glass   |
| <b>Variants (On/Off, 1-10V, DALI)</b> | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)  |

