

**QUARTER 2 (QU-31402)**



**Product description**

Medium




**Luminaire Structure**


- Two cable entries for through wiring
- Clear toughened glass

- Integral control gear


**Optic**



**Product colour**



**Special finishes upon request**



**QUARTER 2 (QU-31402)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	2x24 LED
<b>Power</b>	75 W
<b>Lumen</b>	8814 - 10079 lm
<b>Efficacy</b>	118 - 134 lm/W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz

<b>Optic</b>	M, W, EW, T1, T2, T3, T4, ME 30°, 56°, 112°, 145°x75°, 136°x58°, 123°x93°, 105°x69°, 140°x63°
<b>Optic value</b>	
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Bug</b>	B2-U0-G2, B3-U0-G0, B3-U0-G3, B4-U0-G0, B4-U0-G1
<b>ULR</b>	0%
<b>ULOR</b>	0%
<b>CIE flux code n°3</b>	96, 97, 98, 99
<b>Dimming type</b>	On/Off, 1-10V, DALI

<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Weight</b>	9.3 kg
<b>Operating temperature</b>	-20 °C to 40 °C
<b>Through wiring</b>	Two cable entries for through wiring
<b>Lens / Reflector / Optic</b>	Clear toughened glass
<b>Variants (On/Off, 1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

QU-31402

