


ROCKY 1 (RC-80001)**Product description**


118x118 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management

- Propriety lens design for high LOR
- Adjustable: Tilt 30°

- Remote driver is included


Optic**N****M****W****Product colour**08 - Glossy White
(RAL 9010)09 - Glossy Black
(HB451022M)

ROCKY 1 (RC-80001)

Technical information

Material	Aluminium	Input voltage	500 mA, 15 VDC	Operating temperature	-20 °C to 40 °C
Light source	5 LED	Optic	N, M, W	MacAdam Ellipse	3 SDCM
Power	9 W	Optic value	19°, 31°, 48°	Lifetime L90B10 (hours)	> 120,000
Lumen	612 - 750 lm	CCT / CRI	3000K CRI80, 4000K CRI80	Lifetime L80B10 (hours)	> 120,000
Efficacy	68 - 83 lm/W	Dimming type	On/Off, 1-10V, DALI, Trailing edge	Lifetime L80B50 (hours)	> 120,000
Driver option	Remote driver (included)	Product colours	Glossy White, Glossy Black	Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Driver	Constant current (CC)	Weight	0.49 kg.		

RC-80001



Accessories



DALI Control System
Control-DALI