


**ROCKY 2 (RC-80021)****Product description**


147x147 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management

- Propriety lens design for high LOR
- Adjustable: Tilt 30°

- Remote driver is included

**Optic****N****M****W****Product colour**08 - Glossy White  
(RAL 9010)09 - Glossy Black  
(HB451022M)

**ROCKY 2 (RC-80021)**


**Technical information**

|                      |                          |
|----------------------|--------------------------|
| <b>Material</b>      | Aluminium                |
| <b>Light source</b>  | 9 LED                    |
| <b>Power</b>         | 15 W                     |
| <b>Lumen</b>         | 1095 - 1283 lm           |
| <b>Efficacy</b>      | 73 - 86 lm/W             |
| <b>Driver option</b> | Remote driver (included) |
| <b>Driver</b>        | Constant current (CC)    |

|                        |                                    |
|------------------------|------------------------------------|
| <b>Input voltage</b>   | 500 mA, 27 VDC                     |
| <b>Optic</b>           | N, M, W                            |
| <b>Optic value</b>     | 15°, 26°, 39°                      |
| <b>CCT / CRI</b>       | 3000K CRI80, 4000K CRI80           |
| <b>Dimming type</b>    | On/Off, 1-10V, DALI, Trailing edge |
| <b>Product colours</b> | Glossy White, Glossy Black         |
| <b>Weight</b>          | 0.92 kg.                           |

|                                |   |
|--------------------------------|---|
| <b>Operating temperature</b>   | -20 °C to 40 °C   |
| <b>MacAdam Ellipse</b>         | 3 SDCM  |
| <b>Lifetime L90B10 (hours)</b> | > 120,000   |
| <b>Lifetime L80B10 (hours)</b> | > 120,000   |
| <b>Lifetime L80B50 (hours)</b> | > 120,000   |
| <b>Variants (1-10V, DALI)</b>  | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0) |

**RC-80021**



**Accessories**



DALI Control System  
Control-DALI