


ROCKY 2 (RC-80031)**Product description**


147x147 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management

- Propriety lens design for high LOR
- Adjustable: Tilt 30°

- Remote driver is included

Optic**N****M****W****Product colour**08 - Glossy White
(RAL 9010)09 - Glossy Black
(HB451022M)

ROCKY 2 (RC-80031)


Technical information

Material	Aluminium
Light source	12 LED
Power	20 W
Lumen	1512 - 1720 lm
Efficacy	76 - 86 lm/W
Driver option	Remote driver (included)
Driver	Constant current (CC)

Input voltage	500 mA, 36 VDC
Optic	N, M, W
Optic value	15°, 26°, 39°
CCT / CRI	3000K CRI80, 4000K CRI80
Dimming type	On/Off, 1-10V, DALI, Trailing edge
Product colours	Glossy White, Glossy Black
Weight	1.00 kg.

Operating temperature	-20 °C to 40 °C
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 120,000
Lifetime L80B10 (hours)	> 120,000
Lifetime L80B50 (hours)	> 120,000
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

RC-80031



Accessories



DALI Control System
Control-DALI