


**ROY 3 (RY-80101)****Product description**

4 Busbar 3 Circuit

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Propriety lens design for high LOR
- Adjustable: Tilt 90°, Rotation 355°
- Integral control gear
- Universal adaptor compatible with any track

**Optic****Product colour**

**ROY 3 (RY-80101)**

**Technical information**

<b>Material</b>	Aluminium	<b>Optic</b>	N, M, W	<b>Product colours</b>	Glossy White, Glossy Black
<b>Light source</b>	9 LED	<b>Optic value</b>	14°, 25°, 40°	<b>Weight</b>	0.91 kg.
<b>Power</b>	15 W	<b>CCT / CRI</b>	3000K, 4000K	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Lumen</b>	1050 - 1272 lm	<b>Bug</b>	B2-U0-G0	<b>MacAdam Ellipse</b>	3 SDCM
<b>Efficacy</b>	70 - 85 lm/W	<b>ULR</b>	0%	<b>Lifetime L90B10 (hours)</b>	> 120,000
<b>Driver option</b>	Integral control gear	<b>ULOR</b>	0%	<b>Lifetime L80B10 (hours)</b>	> 120,000
<b>Driver</b>	Constant current (CC)	<b>CIE flux code n°3</b>	100, 99	<b>Lifetime L80B50 (hours)</b>	> 120,000
<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Dimming type</b>	On/Off		Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
				<b>Variants (On/Off)</b>	

RY-80101

