

**SPACE 1 (SP-20556-2)**



**Product description**

Flat top



**Luminaire Structure**

- Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance
- Stainless steel fasteners in grade 316

- Durable silicone rubber gasket
- Clear, impact-resistant, UV-stabilised polycarbonate diffuser


- Sandblast finishing aluminum reflector

**Optic**




G

**Product colour**



**Special finishes upon request**



**SPACE 1 (SP-20556-2)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	1 COB
<b>Power</b>	41 W
<b>Lumen</b>	1099 - 1113 lm
<b>Efficacy</b>	27 lm/W
<b>Driver option</b>	Integral control gear

<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	G
<b>Optic value</b>	175°x 177°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Dimming type</b>	On/Off, 1-10V, DALI

<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Weight</b>	10.5 kg
<b>Operating temperature</b>	-20 °C to 40 °C
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 55,000
<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

SPACE 1  
SP-20556-2

