

SPC135100-SC60

89 . - 60

3500

600 15

100X100

-75X315

-22X60 255 [147-200

## 3.5 m - 100x100 mm - Spigot: 60 mm (SPC135100-SC60)



#### Luminaire Structure

- Manufacturing process is in accordance with EN40 standard

- Pre-treated and coated by the high-quality, UV-resistant, powder
- coating for ensuring high corrosion resistance
- Material: Galvanised steel
- Form: Square, straight
- Installing options: Mounting base or anchor bolts on a foundation
- Height options: 2.5 m, 3 m, 3.5 m, 4 m, 5 m, 5.5 m, 6 m
- Diameter/dimension options: 100x100 mm
- Spigot options: 76 mm

## **Technical information**

| Height (mm)                                    | 3500   |
|--|--|
| Diameter / dimension (mm)                      | 100x100  |
| Spigot (mm)                                    | 60   |
| Weight (kg)                                    | 46   |
| Horizontal loads resistance (V ref,0 -<br>m/s) | 50   |
| Luminaire weight (max - kg)                    | 50   |
| Luminaire wind catching area (max - m2)        | 0.25   |
| Material                                       | Galvanised Steel   |
| Product colours                                | Black, Dark Grey, White, Matt Silver,<br>Bronze, Concrete - Urban, Softscape -<br>Urban, Stone - Urban, Corten - Urban,<br>Oak - Woodland, Walnut - Woodland,<br>Pine - Woodland |

We reserve the right to make technical and design changes.

06:43, 09-05-2024



# 3.5 m - 100x100 mm - Spigot: 60 mm (SPC135100-SC60)

### Accessories



We reserve the right to make technical and design changes.

06:43, 09-05-2024