

**SYNDY 2 (SY-20913)**



**Product description**

Oval - Supplied with a cylindrical, straight aluminium pole  
 pole - Height options: 4 - 6 m



**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Extruded aluminium column
- Single cable entry

- One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass


- White coated aluminium reflector on the top of luminaire
- Integral control gear
- Maximum wind load resistance is 120 km/h

**Optic**




G

**Product colour**



**Special finishes upon request**




**SYNDY 2 (SY-20913)**





**Technical information**

<b>Material</b>	Aluminium	<b>Optic value</b>	122°x 120°	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Light source</b>	1 COB	<b>CCT / CRI</b>	3000K, 4000K	<b>Cable</b>	One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
<b>Power</b>	39 W	<b>Bug</b>	B1-U3-G1	<b>Through wiring</b>	Single cable entry
<b>Lumen</b>	1986 - 2491 lm	<b>ULR</b>	4%	<b>Lens / Reflector / Optic</b>	Clear toughened glass, White coated aluminium reflector on the top of luminaire
<b>Efficacy</b>	51 - 64 lm/W	<b>ULOR</b>	4%	<b>MacAdam Ellipse</b>	3 SDCM
<b>Driver option</b>	Integral control gear	<b>CIE flux code n°3</b>	94	<b>Lifetime L90B10 (hours)</b>	> 50,700
<b>Driver</b>	Constant current (CC)	<b>Dimming type</b>	On/Off, 1-10V, DALI	<b>Lifetime L80B10 (hours)</b>	> 63,500
<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	<b>Lifetime L80B50 (hours)</b>	> 63,500
<b>Optic</b>	G	<b>Weight</b>	34.6 kg	<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

SY-20913



**Accessories**

			
Circuit breaker box IP44 <b>A21291</b>	Root mount kit <b>A20691</b>	DALI Control System <b>Control-DALI</b>	4 m - Cylindrical, straight aluminium pole for SYNDY <b>APD140140-SYNDY</b>

**SYNDY 2** (SY-20913)

---

5 m - Cylindrical, straight  
aluminium pole for SYNDY  
**APD150140-SYNDY**

---



---

6 m - Cylindrical, straight  
aluminium pole for SYNDY  
**APD160140-SYNDY**

---