

**TOKYO 2 (TOK-80031)****Luminaire Structure**

- Die-cast aluminium housing
- Adjustable: Tilt 90°, Rotation 350°

- With powder coating
- Remote driver (not included)

- PAR16 GU10 socket, LED and halogen lamps are suitable (up to 30W)

**Optic****M****E****Product colour**

01 - Black (RAL 9011)

03 - White (RAL 9003)

**TOKYO 2 (TOK-80031)**

**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	MR16-GU10
<b>Power</b>	8 W
<b>Lumen</b>	330 - 460 lm
<b>Efficacy</b>	41 - 58 lm/W
<b>Driver option</b>	Remote driver (not included)

<b>Driver</b>	Constant voltage (CV)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	N, M, VW, E
<b>Optic value</b>	13°, 23°, 38°, 51° x 12°
<b>CCT / CRI</b>	3000K CRI95, 4000K CRI90
<b>ULR</b>	0%

<b>ULOR</b>	0%
<b>CIE flux code n°3</b>	99
<b>Dimming type</b>	On/Off
<b>Product colours</b>	Black, White
<b>Operating temperature</b>	-20 °C to 40 °C

TOK-80031

