


TUSCON 1 (TS-80011)**Product description**


118x478 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management

- Propriety lens design for high LOR
- Adjustable: Tilt 30°

- Remote driver is included

Optic**Product colour**

TUSCON 1 (TS-80011)

Technical information

Material	Aluminium
Light source	7 LED
Power	47 W
Lumen	2656 - 3832 lm
Efficacy	55 - 80 lm/W
Driver option	Remote driver (included)
Driver	Constant current (CC)

Input voltage	500 mA, 21 VDC
Optic	N, M, W
Optic value	15°, 26°, 35°
CCT / CRI	3000K CRI80, 4000K CRI80
Dimming type	On/Off, 1-10V, DALI, Trailing edge
Product colours	Glossy White, Glossy Black
Weight	2.14 kg.

Operating temperature	-20 °C to 40 °C
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 120,000
Lifetime L80B10 (hours)	> 120,000
Lifetime L80B50 (hours)	> 120,000
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

Tuscon 1

