


TUSCON 3 (TS-80041)**Product description**


147x579 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management

- Propriety lens design for high LOR
- Adjustable: Tilt 30°

- Remote driver is included

Optic**Product colour**

TUSCON 3 (TS-80041)

Technical information

Material	Aluminium	Input voltage	1050 mA, 27 VDC	Operating temperature	-20 °C to 40 °C
Light source	18 LED	Optic	N, M, W	MacAdam Ellipse	3 SDCM
Power	115 W	Optic value	15°, 27°, 42°	Lifetime L90B10 (hours)	> 120,000
Lumen	9936 - 11348 lm	CCT / CRI	3000K CRI80, 4000K CRI80	Lifetime L80B10 (hours)	> 120,000
Efficacy	86 - 98 lm/W	Dimming type	On/Off, 1-10V, DALI	Lifetime L80B50 (hours)	> 120,000
Driver option	Remote driver (included)	Product colours	Glossy White, Glossy Black	Variants (DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Driver	Constant current (CC)	Weight	5.07 kg.		

Tuscon 3

