


TAURAS 1 (TU-10136-1-SB)**IP55****IK08****Product description**

Ø160 - 771 mm - Dome top - With integrated security core (Anti-traffic)

**Luminaire Structure**

- Die-cast aluminium housing
- Extruded aluminium column
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear UV-stabilised polycarbonate diffuser
- Sandblast finishing aluminium reflector
- Integral control gear

Optic

**G**

TAURAS 1 (TU-10136-1-SB)


Technical information

| | |
|----------------------|-----------------------|
| Light source | 1 COB |
| Power | 41 W |
| Lumen | 962 - 974 lm |
| Efficacy | 23 - 24 lm/W |
| Driver option | Integral control gear |
| Driver | Constant current (CC) |
| Input voltage | 220-240 V 50/60 Hz |

| | |
|--------------------------|--------------------------|
| Optic | G |
| Optic value | 360° |
| CCT / CRI | 3000K CRI80, 4000K CRI80 |
| Bug | B1-U3-G1 |
| ULR | 30% |
| ULOR | 30% |
| CIE flux code n°3 | 75 |

| | |
|---------------------------------|---|
| Dimming type | On/Off, 1-10V, DALI |
| Weight | 7.0 kg |
| Operating temperature | -20 °C to 40 °C |
| Cable | One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable |
| Through wiring | Single cable entry |
| Lens / Reflector / Optic | Clear UV-stabilised polycarbonate diffuser, Sandblast finishing aluminium reflector |
| Variants (1-10V, DALI) | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0) |

TU-10136-1-SB



Accessories



DALI Control System
Control-DALI