

## VEKTER 2 (VK-30003)



### Product description

Large



### Luminaire Structure

- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)

- Durable silicone rubber gasket
- Clear toughened glass
- High-efficiency PMMA lens
- Integral control gear

- Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible

### Optic



M W EW T2



T3 T4

### Product colour




01 - Black (RAL 9011) 02 - Dark Grey (RAL 7043) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)

### Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban




SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

**VEKTER 2 (VK-30003)**

**Technical information**

<b>Material</b>	Aluminium	<b>Optic value</b>	32°, 52°, 108°, 140°x51°, 140°x72°, 97°x82°	<b>Through wiring</b>	Two cable entries for through wiring
<b>Light source</b>	24 LED	<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80	<b>Lens / Reflector / Optic</b>	Clear toughened glass, High-efficiency PMMA lens
<b>Power</b>	37 W	<b>Bug</b>	B1-U0-G1, B2-U0-G0, B3-U0-G0	<b>MacAdam Ellipse</b>	3 SDCM
<b>Lumen</b>	4509 - 5143 lm	<b>ULOR</b>	0%	<b>Lifetime L90B10 (hours)</b>	> 90,000
<b>Efficacy</b>	122 - 139 lm/W	<b>CIE flux code n°3</b>	97%, 98%, 99%	<b>Lifetime L80B10 (hours)</b>	> 90,000
<b>Driver option</b>	Integral control gear	<b>Dimming type</b>	On/Off, 1-10V, DALI	<b>Lifetime L80B50 (hours)</b>	> 90,000
<b>Driver</b>	Constant current (CC)	<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
<b>Input voltage</b>	220-240 V 50/60 Hz				
<b>Optic</b>	M, W, EW, T2, T3, T4	<b>Weight</b>	4.9 kg		
		<b>Operating temperature</b>	-20 °C to 40 °C		

VK-30003



**Accessories**



Surface mounting box for easy cabling (VEKTER 2)  
**SCE-VEKTER-2**