

**YORK 4 (YOK-80031)****Product description**

600x600 mm - Perforated cover

**Luminaire Structure**

- Formed sheet steel body with powder coating
- White painted metal sheet
- Stainless steel fasteners in grade 316
- Micro prismatic, opal, perforated cover and double parabolic louvre options
- Remote driver is included
- Two sizes: 600x600 mm & 300x1200 mm

**Product colour**

03 - White (RAL 9003)


10 - White (RAL 9016)

**YORK 4 (YOK-80031)**

**Technical information**

<b>Material</b>	Aluminium	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>CIE flux code n°3</b>	96
<b>Light source</b>	2 x 60 LED	<b>Optic</b>	G	<b>Dimming type</b>	On/Off, DALI
<b>Power</b>	50 W	<b>Optic value</b>	107°x124°	<b>Product colours</b>	White
<b>Lumen</b>	3800 lm	<b>CCT / CRI</b>	4000K CRI80	<b>Weight</b>	5.0 kg
<b>Efficacy</b>	76 lm/W	<b>Bug</b>	B2-U1-G1	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Driver option</b>	Integral control gear	<b>ULR</b>	0%	<b>Variants (On/Off, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
<b>Driver</b>	Constant current (CC)	<b>ULOR</b>	0%		

YOK-80031



**Accessories**



DALI Control System  
Control-DALI